

### Capture interface options

-i <interface>	name or index of interface (defaults to 1st non-loopback)
-f <capture filter>	packet filter in libpcap filter syntax
-p	disable capturing in promiscuous mode
-B <buffer size>	size of kernel buffer (def. 2MB)
-y <link type>	link layer type (def. first appropriate)
-D	print list of interfaces and exit
-L	print list of link layer types and exit

### Capture stop conditions

-c <packet count>	stop after n packets (def. infinite)
-a <autostop condition>	duration:<num> - stop after <num> seconds filesize:<num> - stop file after <num> KB files:<num> - stop after <num> files

### Capture output

-b <ringbuffer opt>	<b>duration:&lt;num&gt;</b> - switch to next file after <num> seconds <b>filesize:&lt;num&gt;</b> - switch to next file after <num> KB <b>files:&lt;num&gt;</b> - ringbuffer: replace after <num> files
---------------------	---

### Processing options

-2	perform a two-pass analysis
-R <read filter>	packet read filter in Wireshark display filter syntax
-Y <display filter>	packet display filter in Wireshark display filter syntax
-n	disable all name resolutions
-N <name resolve flags>	enable specific name resolutions: "mn-tCd"
-d <layer type>=<selector>,<decode_as_protocol>	decode as, see the <a href="#">tshark man page</a> for details
-H <hosts file>	read a list of entries from a hosts file which will then be written to a capture file (implies -W n)
--disable-protocol <proto_name>	disable dissection of <proto_name>

### Processing options (cont)

--enable-heuristic <short_name>	enable dissection of heuristic protocol
--disable-heuristic <short_name>	disable dissection of heuristic protocol

### Miscellaneous options

-h	display help and exit
-v	display version info and exit
-o <name>:<value>	override preference setting
-K <keytab>	keytab file to use for Kerberos decryption
-G <report>	dump one of several available reports and exit default report="fields" use -G ? for more help

### RPCAP options

-A <user>:<password>	use RPCAP password authentication
----------------------	-----------------------------------

### Input file options

-r <infile>	set the filename to read from (- to read from stdin)
-------------	--

### Output file options

-w <outfile> >	write packets to a pcap-format file named "outfile" (or to standard output file for -)
-C <config profile>	start with specified configuration profile
-F <output file type>	set the output file type (def. is pcapng) an empty -F option will list the file types
-V	add output of packet tree (Packet Details)
-O <protocols>	only show packet details of these protocols (comma separated)
-P	print packet summary even while writing to file



By **mbwalker**  
[cheatography.com/mbwalker/](https://cheatography.com/mbwalker/)

Not published yet.  
Last updated 8th December, 2020.  
Page 1 of 2.

Sponsored by **Readable.com**  
Measure your website readability!  
<https://readable.com>

### Output file options (cont)

-S <separator>	the line separator to print between packets
-x	add output of hex and ASCII dump (Packet Bytes)
-T pdml ps p-sm text fields	format of text output (def: text)
-e <field>	field to print if -Tfields selected (tcp.port, ws.col.info) this option can be repeated to print multiple fields
-E <fieldsoption>=<value>	set options for output when -Tfields selected: <b>header=y n</b> - switch headers on and off <b>separator=t s &lt;char&gt;</b> - select tab, space, printable character as separator <b>occurrence=f L a</b> - print first, last or all occurrences of each field <b>aggregator=, /s /&lt;char&gt;</b> - select comma, space, printable character as aggregator <b>quote=d s n</b> - select double, single or no quotes for values
-t a ad d dd e r u ud	output format of timestamps (def: r rel. to first)
-u s hms	output format of seconds (def: s - seconds)
-l	flush standard output after each packet
-q	be more quiet on stdout (when using statistics)
-Q	only log true errors to stderr (quieter than -q)

### Output file options (cont)

-g	enable group read access on the output file(s)
-W n	save extra info in the file, if supported n= write network address resolution info
-X <key>:<value>	eXtension options, see <a href="#">tshark man page</a> for details
-z <statistics>	various statistics, see <a href="#">tshark man page</a> for details
--capture-comment <comment>	add a capture comment to the newly created output file ( <b>only for pcapng format</b> )



By **mbwalker**  
[cheatography.com/mbwalker/](https://cheatography.com/mbwalker/)

Not published yet.  
Last updated 8th December, 2020.  
Page 2 of 2.

Sponsored by **Readable.com**  
Measure your website readability!  
<https://readable.com>